



MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label)	CATALOG NUMBER			
Aqua-Gel® II Utility Cable Pulling Lubricant	All "31" Series			
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.			
IDEAL INDUSTRIES, INC.	(815) 895-5181			
ADDRESS (Number, Street, City, State, Zip Code)				
Becker Place, Sycamore, IL 60178				
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101)				
None				
CHEMICAL DESCRIPTION	FORMULA			
Polymer-based Mixture	Proprietary			

SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, I ARC or OSHA 1910(z) (specify)
7732-18-5	<90	Water	No
9038-95-3	<10	Oxirane, Methyl-, Polymer With Oxirane, Monobutyl Ether	No
9003-11-6	<5	Polyoxypropylene-polyoxyethylene Block Copolymer	No
102-71-6, 7732- 18-5, 10246-68- 1, 22919-56-8, 64665-57-2, 693- 23-2	<1	Proprietary Mixture of Ethanol, 2,2',2" Nitrilotris; Water; Nonanoic acid; Triethanolamine salt, Caprylic acid; triethanolamine salt; 1H-Benzotriazole, 4-methyl-,sodium salt; Dodecanedioic acid	No
1310-58-3	<2	20% Potassium Hydroxide	No
52-51-7	<0.1	2-Bromo-2-Nitropropane 1,3 Diol	No
3844-45-9 7757-82-6 7647-14-5	<0.1	Blue Pigment	No

SECTION II - PHYSICAL DATA

BOILING POINT	SPECIFIC GRAVITY (H ₂ O=1)	PERCENT VOLATILE BY VOLUME (%)		
212 °F 100°C	0.98	<90		
SOLUBILITY IN WATER	pH =	PERCENT SOLID BY		
Infinite	7.0 - 8.0	WEIGHT (%) ~10		
APPEARANCE AND ODOR		IS MATERIAL: LIQUID SOLID (GEL)		
Clear blue	GAS PASTE			

SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	None	method used C.O.C	FLAMMABLE LIMITS	LEL	UEL
				None	None
EXTINGUISHING	MEDIA				
Use extinguishing media suitable for surrounding materials.					
SPECIAL FIRE FI	GHTING PROCE	DURES			
			None		
UNUSUAL FIRE AND EXPLOSION HAZARDS					
			None		

^{*} None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

SECTION IV - HEALTH HAZARD INFORMATION

				.,,	<u> </u>	
EFFECTS OF OVI	EREXPOSURE - Cond	ditions to A		octod	l Inon prol	ongod contact, may cause temperary eye
None normally expected. Upon prolonged contact, may cause temporary eve discomfort.						
THRESHOLD LIM	IT VALUE					
PRIMARY ROLITE	S OF ENTRY Inhalat	ion □ S	N.I kin Contact ☑ Other (specify)	<u>. </u>		
	RST AID PROCEDURE		Carlo (oposity)			
SKIN CONTACT:	RST AID PROCEDURE		sh with soap and water.			
EYE CONTACT:			Flush wit	h watei	•	
INGESTION:	-	S				
	L	JO NOT INC	duce vomiting. Consult phy SECTION V - RE			
	UNSTABLE CONDITIONS TO AVOID					
STABILITY	CTABLE	V	Avoid prolonged storage at temperatures exceeding 190 F.			temperatures exceeding 190 F.
	STABLE	Х				
INCOMPATIBILITY	Y (materials to avoid)		Avoid strong oxid	izare a	nd nitritas	
HAZARDOUS DE	COMPOSTION PROD					
	MAY OCCUR		<u>e unlikelv event of combusti</u> CONDITIONS TO AVOID	on of d	ried residu	ue. oxides and nitrogen may be released.
HAZARDOUS POLYMERIZATIO		,			1	None
I OLIMENIZATIO	WILL NOT OCCU	IR X				
		- ;	SECTION VI - SPILL AN	D LEA	K PROC	CEDURES
STEPS TO BE TA	KEN IF MATERIAL IS					
dangerously	v slipperv		vvipe up. snovel or vacuum	spilled	materiai.	Clean up spills immediately as they can be
WASTE DISPOSA						
		Com	olv with Federal, state and l	ocal red	ulations f	or solid landfill.
CERCLA (Superfu	nd) REPORTABLE Q	UANTITY (i	n lbs)			
			N/.	A		
RCRA HAZARDO	US WASTE NO. (40C	FR 261.33)	N/	Α		
VOLATILE ORGA	NIC COMPOUND (VC	C) (as pacl	kaged, minus water) 1.7 gm	o / Itr		
³ Theoretical	lb/gal N/A		1.7 पा	3 Analytic	cal lb/	/gal N/A
		SEC	TION VII - PERSONAL P	ROTE	CTION II	NEORMATION
RESPIRATORY P	ROTECTION (specify					
	_OCAL EXHAUST (Sp	necify Rate)	None norma None	lv reau	ired. SPECIAL	None
VENTILATION		CHANICAL (General) (Specify Rate)				None
	,		ded in closed areas.		OTHER	Notic
	OVES (specify type) eded -Neoprene if neo	cessary	EYE PROTECTION (specify type) None normally re-	quired.	Safely gla	asses or splash goggles recommended.
OTHER PROTEC	TIVE EQUIPMENT					
		Eve	fountain in work area is rec			
PRECAUTIONS T	O BE TAKEN IN HAN	DLING ANI	SECTION VIII - SPEC	JAL P	RECAU	IION5
				atures l	etween 4	0 - 180 F. Avoid freezina.
OTHER PRECAU	TIONS		Keep away from child	ren infa	ants and n	nets
			SECTION IX - ADDITI	ONAL	INFORM	IATION
						ould result in the formation of nitrosamines
			his condition is unlikely to	occu	r.	
N/A = Not Ap	plicable, N.E. =				LIEET DE	
			S MATERIAL SAFETY DA			REPARED BY:
	ames R. MacM			SIGN	ATURE	
	тпте Mgr., Construction Market Development				A Pmh.	
DATE 01/11/2011 Game (. Machiera					James R. MacMurdo	
						V
I				l		