acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

1 Identification

· Product identifier

· Trade name: Ethylbenzene

· Article number: 134380

• CAS Number: 100-41-4 • EC number: 202-849-4

• Index number: 601-023-00-4

- · Application of the substance / the mixture Laboratory chemicals for research and development
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BeanTown Chemical 9 Sagamore Park Road Hudson, NH 03051 USA

Phone: (603) 402-2234 Fax: (603) 402-9713

Email: technical@beantownchem.com

www.beantownchem.com

- · Information department: Technical Support Department
- · Emergency telephone number:

During normal operating hours, please call (603) 402-2234 After hours, please call Chemtrec at (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: ethylbenzene

(Contd. on page 2)

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

100-41-4 ethylbenzene

- · Identification number(s)
- · EC number: 202-849-4
- · Index number: 601-023-00-4

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute

(Contd. on page 4)

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm

BE

· Ingredients with biological limit values:

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eve protection: Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- General Information
- · Appearance:

Form: Liquid
Color: Colorless
Odor: Petrol-like

(Contd. on page 5)

Safety Data Sheet acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reviewed on 11/30/2014 Printing date 03/05/2015

Trade name: Ethylbenzene

	(Contd. of page
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	136 °C (277 °F)
Flash point:	15 °C (59 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	430 °C (806 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	7.8 Vol %
Vapor pressure at 20 °C (68 °F):	9.5 hPa (7 mm Hg)
Density at 20 °C (68 °F):	0.867 g/cm³ (7.235 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	$0.2~\mathrm{g/l}$
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	0.63 mPas
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.0 %
	867.0 g/l / 7.24 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values that	are relevant	for classi	fication:
-----------	-------------	--------------	------------	-----------

100-41-4 ethylbenzene

Oral | LD50 | 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

100-41-4 ethylbenzene

2B

· NTP (National Toxicology Program)

Substance is not listed.

OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

USA

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

(Contd. of page 6)

Transport information		
UN-Number	11311175	
DOT, IMDG, IATA	UN1175	
UN proper shipping name		
DOT	Ethylbenzene	
IMDG, IATA	ETHYLBENZENE	
Transport hazard class(es)		
DOT, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler):	33	
EMS Number:	F-E,S-D	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 5 L	
	On cargo aircraft only: 60 L	
Hazardous substance:	1000 lbs, 454 kg	
IMDG		
Limited quantities (LQ)	IL	
Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
UN "Model Regulation":	UN1175, Ethylbenzene, 3, II	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

Substance is listed.

(Contd. on page 8)

acc. to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Printing date 03/05/2015 Reviewed on 11/30/2014

Trade name: Ethylbenzene

	(Contd. of pa
Chemicals known to cause reproductive toxicity for females:	
Substance is not listed.	
Chemicals known to cause reproductive toxicity for males:	
Substance is not listed.	
Chemicals known to cause developmental toxicity:	
Substance is not listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
100-41-4 ethylbenzene	
TLV (Threshold Limit Value established by ACGIH)	
100-41-4 ethylbenzene	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
Substance is not listed.	
RTECS	
Substance is not listed.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· NFPA ratings (scale 0-4)

Health = 1

Fire = 3

Reactivity = 0

· HMIS ratings (scale 0-4)

Health = 1

Fire = 3

Reactivity = 0

- · Department issuing SDS: Technical Support Department
- · Contact: Technical Support Department
- · Date of preparation / last revision 03/05/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4