

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

The following Safety Data Sheet (SDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Dunn-Edwards Corporation; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following SDS supersedes any previously issued SDS for each product covered. The reader is advised to destroy any obsolete SDS and refer only to this SDS. As permitted by OSHA, each SDS may apply to a class of products which have similar hazards and contents.

Products covered by this SDS are listed below:

ACBL10-0: ACRI-BUILD Flat

ACHS10-0: ACRI-HUES Flat

ACHS30-0: ACRI-HUES Eggshell ACHS50-0: ACRI-HUES Semi-Gloss

ACWC10-0: ACRI-WALL Flat Concentrate **ACWL10-0**: ACRI-WALL Flat Ready-To-Use

ACWL30-0: ACRI-WALL Eggshell

ACWL50-0: ACRI-WALL Semi-Gloss

AQUA10-1: AQUAFALL Flat

AQUA30-1: AQUAFALL Eggshell

AQUA50-1: AQUAFALL Semi-Gloss **ASHL30-0**: ARISTOSHIELD Eggshell

ASHL40-0: ARISTOSHIELD Low Sheen

ASHL50-0: ARISTOSHIELD Low Sneen ASHL50-0: ARISTOSHIELD Semi-Gloss

ASHL70-0: ARISTOSHIELD High Gloss

AWLL50-0: ARISTOWALL Semi-Gloss

AWLL60-0: ARISTOWALL Gloss

BIPR00-1: BLOCK-IT Premium

BRPR00-2-RO: BLOC-RUST Premium, Red Oxide

BRPR00-2-WH: BLOC-RUST Premium, White

DURA50-0: DURAFLO Semi-Gloss

DURA50-1: DURAFLO Semi-Gloss

DURA60-0: DURAFLO Gloss

DURA60-1: DURAFLO Gloss

ENCT30-0: ENDURA-COAT Eggshell

ENCT50-0: ENDURA-COAT Semi-Gloss

ENCT60-0: ENDURA-COAT Gloss

ENPR00-0-GR: ENDURAPRIME, Gray

ENPX50-0: ENDURACAT Semi-Gloss

ESPR00-1: EFF-STOP Premium

ESSL00-0: EFF-STOP Select

EVER10-0: EVEREST Flat EVER20-0: EVEREST Velvet

EVER30-0: EVEREST Eggshell

EVER50-0: EVEREST Semi-Gloss

EVSH10-2: EVERSHIELD Flat

EVSH10-3: EVERSHIELD Flat

EVSH20-2: EVERSHIELD Velvet

EVSH20-3: EVERSHIELD Velvet

EVSH30-2: EVERSHIELD Eggshell

EVSH30-3: EVERSHIELD Eggshell

EVSH40-2: EVERSHIELD Low-Sheen

EVSH40-3: EVERSHIELD Low-Sheen

EVSH50-2: EVERSHIELD Semi-Gloss

EVSH50-3: EVERSHIELD Semi-Gloss

EVSH60-2: EVERSHIELD Gloss

EVSH60-3: EVERSHIELD Gloss

EZPR00-1: EZ-PRIME Premium

FPSL00-1: FLEX-PRIME Select

FTXS10-0: FLEX-TEX Smooth

IKPR00-1: INTER-KOTE Premium Zero VOC

PMCE10-0: CONTRACTOR'S EDGE Flat

PMCE30-0: CONTRACTOR'S EDGE Eggshell

PMCE50-0: CONTRACTOR'S EDGE Semi-Gloss

PRWL00-0: PREP-WALL Drywall Surface Conditioner

QKWL10-0: QUIK-WALL Flat

continued

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS continued

SBPR00-0: Smooth BLOCFIL Premium
SBSL00-1: Smooth BLOCFIL Select
SFSL00-1: SURFACO Select
SLPR00-2: SUPER-LOC Premium
SPMA10-1: SUPREMA Flat
SPMA20-1: SUPREMA Velvet
SPMA30-0: SUPREMA Eggshell
SPMA40-0: SUPREMA Low Sheen
SPMA50-0: SUPREMA Semi-Gloss
SSHL10-0: SPARTASHIELD Flat
SSHL20-0: SPARTASHIELD Velvet
SSHL30-0: SPARTASHIELD Eggshell
SSHL40-0: SPARTASHIELD Low Sheen

SSHL50-1: SPARTASHIELD Semi-Gloss SSHL60-1: SPARTASHIELD Gloss SSHV10-0: SPARTASHIELD VA Flat SWLL10-0: SPARTAWALL Flat

SWLL20-1: SPARTAWALL Velvet **SWLL30-1**: SPARTAWALL Eggshell **SWLL40-1**: SPARTAWALL Low Sheen **SWLL50-1**: SPARTAWALL Semi-Gloss

SWLR10-0: SUPER-WALL Flat Ready-To-Use

SZRO10-0: SPARTAZERO Flat **SZRO20-0**: SPARTAZERO Velvet **SZRO30-0**: SPARTAZERO Eggshell **SZRO40-0**: SPARTAZERO Low Sheen **SZRO50-0**: SPARTAZERO Semi-Gloss **UGPR00-1**: ULTRA-GRIP Premium

UGSL00-1: ULTRA-GRIP Select Zero VOC

ULDM00-0-GR: ULTRASHIELD DTM Gray Primer **ULDM50-0**: ULTRASHIELD DTM Semi-Gloss Paint **ULGM00-0**: ULTRASHIELD Galvanized Metal Primer **ULMS00-0**: ULTRASHIELD Multi-Surface Primer

ULSB10-0: ULTRA-SCRUB Flat

ULSH40-0: ULTRASHIELD Low Sheen Paint **ULSH60-0**: ULTRASHIELD Gloss Paint

VNPL00-0: VINYLASTIC Plus

VNPR00-1: VINLYLASTIC Premium Ultra-Low VOC

VNSL00-1: VINYLASTIC Select Zero VOC W 350: Interior W/B Acrylic Clear Finish

W 360V: ENDURASEAL
W 370: ENDURAWALL
W 615: ACOUSTIKOTE
W 2456V: Latex Roof Coating
W 5361: Athletic Field Striping Paint
W 6139: Acrylic Elastomeric Coating AZ

W 6160E: VERSAGLO
W 6220E: VERSAGLOSS
W 6230E: VERSAWALL
W 6240: VERSAFLAT
W 6250E: VERSASATIN

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION: MANUFACTURER: DUNN-EDWARDS CORPORATION

SEE COVER PAGE FOR LIST OF PRODUCTS COVERED 4885 EAST 52ND PLACE

LOS ANGELES, CA 90058-5507

SDS DATE: 09/23/2019

PRODUCT TYPE: WATERBORNE PAINT RECOMMENDED USE: ARCHITECTURAL COATING

EMERGENCY PHONE: 1-800-222-1222 OTHER CALLS: (323) 826-2663 FAX NUMBER: (323) 771-1611

HMIS CODES: H F R PP 0 0 0 E



SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: NOT A HAZARDOUS SUBSTANCE OR MIXTURE

GHS LABEL ELEMENTS: [NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.]

SIGNAL WORD: (NONE REQUIRED) HAZARD STATEMENT: (NONE REQUIRED)

PICTOGRAM: (NONE REQUIRED)

PRECAUTIONARY STATEMENTS:

PREVENTION: DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS,

SPRAY MIST AND SANDING DUST. WEAR APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING. AVOID CONTACT WITH SKIN AND EYES.

CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

RESPONSE: CLEAN UP SPILLS WITH INERT ABSORBENT MATERIAL, SUCH AS CLAY GRANULES, PAPER

OR CLOTH WIPES. ALLOW TO DRY BEFORE DISPOSAL.

STORAGE & DISPOSAL: KEEP BETWEEN 40°F AND 110°F AT ALL TIMES. DISPOSE OF CONTAINER AND CONTENTS

IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

HAZARDS NOT OTHERWISE CLASSIFIED: NONE.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:

CHEMICAL NAME COMMON NAME / SYNONYMS CAS NUMBER CONCENTRATION (%WT)

NO REPORTABLE HAZARDOUS INGREDIENTS.

NOTE: EXPOSURES TO POSSIBLE HAZARDOUS INGREDIENTS BELOW REPORTING THRESHOLDS CAN BE MINIMIZED OR AVOIDED BY FOLLOWING RECOMMENDED PROCEDURES FOR SAFE HANDLING, STORAGE, DISPOSAL, AND USE.

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SECTION 4: FIRST-AID MEASURES

EYES: FLUSH EYES WITH FRESH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: HAVE VICTIM DRINK 1 OR 2 GLASSES OF WATER TO ENSURE DILUTION.

INHALATION: MOVE VICTIM TO FRESH AIR.

MOST IMPORTANT SYMPTOMS AND EFFECTS: MAY CAUSE MILD IRRITATION TO SKIN AND EYES. GASTROINTESTINAL

AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND

SDS DATE: 09/23/2019

HEADACHE POSSIBLE.

NOTES TO FIRST AID PROVIDERS: CALL FOR MEDICAL ASSISTANCE IF SYMPTOMS PERSIST.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

UNUSUAL FIRE AND EXPLOSION HAZARDS: LIQUID MATERIAL IS NON-COMBUSTIBLE, BUT DRIED FILMS ARE CAPABLE OF

SUPPORTING COMBUSTION WHEN IN CONTACT WITH OPEN FLAMES. CLOSED CONTAINERS CAN DEVELOP INTERNAL PRESSURE AND MAY RUPTURE WHEN

SUBJECTED TO EXTREME HEAT.

HAZARDOUS COMBUSTION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SPECIAL EQUIPMENT & PRECAUTIONS: USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES. OBSERVE

RECOMMENDED PROCEDURES FOR HANDLING ORDINARY COMBUSTIBLE

MATERIALS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE

EQUIPMENT, EMERGENCY PROCEDURES: WEAR WATERPROOF GLOVES TO AVOID SKIN CONTACT. KEEP CHILDREN AND

PETS AWAY FROM SPILLED LIQUID. PREVENT LIQUID FROM ENTERING DRAINS.

METHODS AND MATERIALS FOR

CONTAINMENT AND CLEAN UP: DIKE SPILLED LIQUID WITH INERT MATERIAL, SUCH AS CLAY GRANULES. SCOOP

UP EXCESS LIQUID AND POUR INTO CONTAINER. USE PAPER OR CLOTH WIPES

TO CLEAN UP SMALL SPILLS. ALLOW TO DRY BEFORE DISPOSAL.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PRECAUTIONS: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STACK CONTAINERS MORE THAN

THREE HIGH. SECURE LOADS AGAINST SHIFTING DURING TRANSPORTATION. USE ONLY

AN APPROPRIATE TOOL TO OPEN CONTAINERS.

SAFE STORAGE CONDITIONS: STORE IN COOL, WELL-VENTILATED AREA. MAINTAIN TEMPERATURE BETWEEN 40°F AND

110°F. AVOID EXPOSURE TO DIRECT SUNLIGHT, HEAT OR FLAME. INSPECT CONTAINERS

FOR LEAKS PERIODICALLY. ROTATE STOCK, USE OLDER MATERIAL FIRST.

INCOMPATIBILITIES: DO NOT HANDLE OR STORE NEAR WATER-REACTIVE MATERIALS, STRONG OXIDIZERS,

ACIDS OR ALKALIS.

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

ACGIH OSHA EXPOSURE LIMITS

TLV/TWA TWA STEL VAPOR PRESS

SDS DATE: 09/23/2019

HAZARDOUS INGREDIENTS CAS NUMBER %WT PPM PPM MG/M³ PPM MG/M³ mmHg @ TEMP

NO REPORTABLE HAZARDOUS INGREDIENTS.

ENGINEERING CONTROLS: USE SIGNS OR BARRIERS TO RESTRICT ACCESS TO PAINTING WORK AREA.

VENTILATION: NORMAL AIR CIRCULATION SHOULD BE SUFFICIENT; OTHERWISE, USE PORTABLE FANS.

ENSURE ADEQUATE VENTILATION DURING APPLICATION, DRYING AND CURING OF PAINT.

RESPIRATORY PROTECTION: FOR SPRAY APPLICATION, USE A NIOSH-APPROVED PARTICULATE FILTER MASK (N95 OR

HIGHER) TO AVOID BREATHING SPRAY MIST. EXPOSED PERSONS WITH ALLERGIÈS OR ASTHMA MAY NEED AN ORGANIC VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA TC 23C

OR EQUIVALENT).

WHEN SANDING, SCRAPING, OR ENGAGING IN ANY ACTIVITY THAT GENERATES AIRBORNE NUISANCE DUST, WEAR A NIOSH-APPROVED PARTICULATE FILTER MASK (N95 OR

HIGHER) TO AVOID BREATHING DUST. FINISH BY WATER-WASHING ALL SURFACES TO

REMOVÉ DUST.

EYE PROTECTION: USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.

SKIN PROTECTION: USE WATERPROOF GLOVES (LATEX, VINYL, RUBBER, OR NEOPRENE) TO AVOID SKIN

CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING

ARE RECOMMENDED FOR PROTECTION AS NECESSARY.

WORK HYGIENIC PRACTICES: WASH HANDS AND FACE BEFORE EATING OR DRINKING.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: OPAQUE LIQUID DISPERSION VAPOR PRESSURE: SAME AS WATER VAPOR

ODOR: VERY MILD ODOR VAPOR DENSITY: SAME AS WATER VAPOR

ODOR THRESHOLD: (NO INFORMATION AVAILABLE) SPECIFIC GRAVITY: ~1.4 (H2O = 1)

pH AS SUPPLIED: ~8.5 SOLUBILITY IN WATER: PARTLY SOLUBLE

FREEZING POINT: 0° C / 32° F PARTITION COEFFICIENT: (NO INFORMATION AVAILABLE)

BOILING POINT: 100° C / 212° F AUTO-IGNITION TEMP: (NOT APPLICABLE)

FLASH POINT: (NOT APPLICABLE) DECOMPOSTION TEMP: (NO INFORMATION AVAILABLE)

EVAPORATION RATE: SAME AS WATER VISCOSITY: 85 – 115 KU

FLAMMABILITY: (NOT APPLICABLE) PERCENT SOLIDS: BY VOL: ~35% BY WT: ~50%

UPPER EXPLOSIVE LIMIT: (NOT APPLICABLE) PERCENT VOLATILE: BY VOL: ~65% BY WT: ~50%

LOWER EXPLOSIVE LIMIT: (NOT APPLICABLE)

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY NOT KNOWN TO OCCUR UNDER NORMAL CONDITIONS. REACTIVITY:

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID: AVOID STORAGE AT TEMPERATURES BELOW 40° F OR ABOVE 110° F.

INCOMPATIBLE MATERIALS: AVOID WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS AND ALKALIS.

HAZARDOUS DECOMPOSITION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: INHALATION, INGESTION, EYE AND SKIN CONTACT

SYMPTOMS OF OVEREXPOSURE: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND

RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

SDS DATE: 09/23/2019

DELAYED OR CHRONIC EFFECTS: AVAILABLE INFORMATION PROVIDES NO EVIDENCE OF DELAYED OR CHRONIC

HEALTH EFFECTS ASSOCIATED WITH EXPOSURE TO THIS PRODUCT DURING NORMAL USE WITH RECOMMENDED PERSONAL PROTECTION AS NEEDED.

NUMERICAL MEASURES OF TOXICITY: (NO INFORMATION AVAILABLE)

CARCINOGENICITY: NTP? NO. IARC? NO. OSHA? NO. PROP 65? NO.

HAZARDOUS BY-PRODUCTS: SPRAY APPLICATION OF THIS PRODUCT CAN GENERATE SPRAY MIST. WHICH

MAY BE HAZARDOUS TO YOUR HEALTH IF INHALED. RISK DEPENDS ON LEVEL

AND DURATION OF EXPOSURE.

SANDING, SCRAPING, OR OTHERWISE DISTURBING THE DRY FILM OF THIS PRODUCT CAN GENERATE AIRBORNE NUISANCE DUST, WHICH MAY BE

HAZARDOUS TO YOUR HEALTH IF INHALED. RISK DEPENDS ON LEVEL AND

DURATION OF EXPOSURE.

SEE SECTION 8: "EXPOSURE CONTROLS / PERSONAL PROTECTION" FOR INFORMATION ON RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: (NO INFORMATION AVAILABLE)

SECTION 13: DISPOSAL CONSIDERATIONS

COLLECT SPILLED MATERIAL, USED ABSORBENT MATERIAL AND WIPES INTO A SUITABLE WASTE DISPOSAL METHOD:

CONTAINER AND DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. DRY, EMPTY CONTAINERS MAY BE RECYCLED OR DISPOSED OF

AS ORDINARY TRASH.

NON-HAZARDOUS RCRA HAZARD CLASS:

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SECTION 14: TRANSPORT INFORMATION

SDS DATE: 09/23/2019

THIS MATERIAL IS NOT SUBJECT TO DOT, IATA/ICAO, OR IMO/IMDG TRANSPORTATION REGULATIONS. ACCEPTABLE FOR AIR TRANSPORT AS NON-HAZARDOUS GOODS.

UN NUMBER: (NOT APPLICABLE) UN PROPER SHIPPING NAME: (NOT APPLICABLE)

TRANSPORT HAZARD CLASS: (NOT APPLICABLE) PACKING GROUP: (NOT APPLICABLE)

ENVIRONMENTAL HAZARDS: (NOT APPLICABLE) TRANSPORT IN BULK: (NOT APPLICABLE)

SPECIAL PRECAUTIONS: FOLLOW RECOMMENDED PROCEDURES FOR SAFE HANDLING AND STORAGE.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA: ALL COMPONENTS ARE LISTED IN TSCA INVENTORY OR EXEMPT.

CERCLA: NOT LISTED AS A HAZARDOUS SUBSTANCE.

SARA TITLE III: NOT LISTED AS A HAZARDOUS SUBSTANCE.

311/312 HAZARD CATEGORIES: (NOT APPLICABLE)
313 REPORTABLE INGREDIENTS: (NOT APPLICABLE)
STATE REGULATIONS: (NOT APPLICABLE)

SECTION 16: OTHER INFORMATION

DATE OF PREPARATION: SEPTEMBER 23, 2019

PREPARER INFORMATION: DUNN-EDWARDS CORPORATION

ENVIRONMENTAL AFFAIRS DEPARTMENT

PHONE: (323) 826-2663

DISCLAIMER: THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS

FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR

CIRCUMSTANCES.